

HDI-98 EDGE

HDI edge
NEW GENERATION

98" Multi-touch Screen

HDI Edge multi touch screens incorporate 20 points of touch.

Complete with Android 8.0, the system is completely plug and play, with no drivers necessary for interaction.


All HDi screens work with Windows, OSX, Linux, Android and Chrome operating systems.

The screen's 4K resolution, LED high brightness backlight and wide screen format provides an ideal medium for presentation, interaction and collaboration.

There are ample I/O ports that would suit any audio-visual environment, making the HDi Edge a must-have companion for education, government and the corporate sector.

HDI Edge multi touch screens come ready for easy wall or Mobile stand installation.

4K 4K resolution

 IR technology

 4 mm toughened glass

 Mobility Options



Features

- IR Technology
- 4K resolution (3840 x 2160 px)
- Powered by Android 8.0
- Multi-touch – up to 20 touch points
- Pre-installed interactive apps
- Integrated inbuilt sound bar
- OPS Slot
- Qwizdom OKTOPUS™ licenses (2x User & 5x Collaboration)
- HDi Sketch™ app
- Mobile and electric height-adjustable options available
- 3 Year warranty
- Ships with wall-mount bracket



TECHNICAL SPECIFICATIONS

Resolution	Up to 3840 x 2160 @ 60Hz
Display Features	LED backlight
Screen dimension	98" / 2477mm
Set dimension	87.71" (L) x 52.28" (H) x 3.89" (W) / 2227mm (L) x 1328mm (H) x 99mm (W) Not including base
Temperature / Humidity	0°C ~ 40° / ≤80%
Net weight	TBC KGS / TBClb
Aspect Ratio	16:9
Brightness	500cd/m2
Contrast	1300:1
Colours	10bit, 1.07 Billion colours
View Angle	178°
Screen Mode	16:9/4:3/dot to dot/full screen
Video Mode	PAL, NTSC, SECAM
Sound Mode	D/K, B/G, I, M
Support Resolution	1280x960 / 1280x1024 / 1360x768 / 1440x900 / 1600x1200 / 1920x1080 / 3840 x 2160@60Hz
Voltage range	AC 100- 240V~, v-50/60Hz
Power range	Standby Power <1W - Working 450W approximately
Audio	15W x 15W internal speakers

INPUTS

CVBS/Audio input	1 x MINI (black)
YPbPr	1 x MINI (black)
SD Card	1 x SD Card
Network	1 x RJ45 IN
USB input	Front: 1 x USB-A 3.0 , 2 x USB-A 2.0 Rear: 1 x USB-A 3.0 , 1 x USB-A 2.0
PC RGB input	1 x D-USB 15pin
PC audio input	1 x 3.5 stereo audio-in jack
HDMI input	3 x HDMI-A, one in front
HDMI format	2 x HDMI 2.0 (back), 1 x HDMI 1.4 (front, Max support FHD@60Hz)
Interactive control input	2 x USB-B, one in front
USB file system	FAT32, FAT16, NTFS (NTFS compressed file is not supported)
DP	Display Port Input 1.2
RS-232	9 PIN D-SUB

OUTPUTS

CVBS/Audio out	1 x MINI (Black)
Headphone	1 x Earphone Jack
SPDIF output	1 x RCA
Touch	Pass through touch

TEAMBOARD ANDROID™/OS™ SPECIFICATION

CPU	2*ARM Cortex A73 1.5GHz
	2*ARM Cortex A53 1.5GHz
GPU	ARM MaliG51 450MHz
Flash	32GB Build in EMMC
SDRAM	4GB DDR4
Android Version	8.0
SD Card	Support MAX 32GB SD Card
WIFI	IEEE802.11 a/b/g/n 2.4 GHz + 5.0GHz

TOUCH PARAMETERS

Touch points	Up to 20 point multi-touch
Writing mode	Finger, stylus or any non-transparent object
Positioning technology	IR technology
Positioning accuracy	+/-2mm
Positioning resolution	4096 x 4096
Writing response time	First point < 8ms, consecutive < 4ms
Cursor speed	>180 dot/sec
Interactive touch control	USB plug and play
Operating system	Windows / Linux / Mac / Android / Chrome
PC response	System auto response



MOBILITY solutions

At HDi we pride ourselves on designing and building customised solutions to solve many bespoke problems.

Remarks:

Above mentioned parameters are for Standard models and are subject to change without notice. * Not all applications are compatible with Android 8.0.

